

FIRE EXTINGUISHERS

Fireblitz a new name but from a production team with over 25 years experience in the manufacture of quality marine fire extinguishers. Convey this confidence to your customers in the knowledge that they have purchased a quality product at the right price that can be relied upon

A Rating is for fires containing solid (carbonaceous) materials

B Rating is for flammable liquids, including petrol, diesel and oil.

C Rating is for gaseous fires

- 5 year warranty
- Controlled discharge
- Manufactured under BS EN ISO 9001:2000

Factory Sealed BC Powder Alpha 600 and Beta 950

- Manufactured to the requirements of BS 6165:2002 (Kitemark 2009)
- Manufactured in the UK
- Aluminium lightweight body
- Suitable for B & C Fire classifications
- Safe for use on electrical equipment
- Supplied with mounting bracket

Model	Part No	Capacity	Fire Rating	Height/dia.	Discharge
Alpha 600	186987	600g	13B	285 x 98	6 secs
Beta 950	187017	950g	34B	325 x 102	8 secs

Factory Sealed BC Powder Omega 1000

- Manufactured to the requirements of EN3
- Fire rating tested BRE / LPCB
- Manufactured in the UK
- Aluminium lightweight body
- Pressure gauge fitted in canister base
- Suitable for B & C Fire classifications
- Safe for use on electrical equipment
- Powder coated, steel wire bracket

Model	Part No	Capacity	Fire Rating	Height/dia.	Discharge
Omega 1000	187018	1kg	34B	312 x 110	8 secs

Refillable ABC Powder Extinguishers FBP1, FBP2 and FBP4

Meets the recommendations of the RYA and British Waterways Joint Boat Safety Scheme.

- FBP1 and FBP2 Third party accredited to EN3 by DNV
- FBP1 and FBP2 MED Ship's Wheel approved
- FBP4 Third party accredited to EN3 and Kitemarked
- Suitable for A, B & C Fire classifications
- Safe for use on electrical equipment
- Supplied with mounting bracket

Model	Part No	Capacity	Fire Rating	Height/dia.	Discharge
FBP1	187019	1kg	5A/34B	335 x 125	10 secs
FBP2	187020	2kg	13A/70B	400 x 135	10 secs
FBP4	187021	4kg	21A/144B	485 x 220	14 secs


Fireblitz
extinguisher

NEW



Fireblitz extinguisher

NEW



Automatic ABC Dry Powder Fire Suppression Units FBAP1 and FBAP2

- Compact and economical automatic extinguisher
- Manufactured in the UK
- Suitable for A, B & C Fire classifications
- Safe for use on electrical equipment
- Powder coated, steel wire bracket

Model	Part No	Capacity	Compartment Size	Height/dia.	Discharge
FBAP1	187022	1kg	1m ²	340 x 125	10 secs
FBAP2	187023	2kg	2m ²	385 x 135	10 secs

Automatic Ozone Friendly Fire Suppression Units FBAG1 and FBAG2

- FE36 TM Clean agent ("Drop In" Halon replacement)
- Zero ozone depletion
- Manufactured in the UK
- Suitable for B & C Fire classifications
- Safe for use on electrical equipment
- Powder coated, steel wire bracket

Model	Part No	Capacity	Compartment Size	Height/dia.	Discharge
FBAG1	187024	1kg	1.7m ³	340 x 125	8 secs
FBAG2	187025	2kg	3.4m ³	385 x 135	8 secs

Fire Blanket

- Rigid ABS Container
- Complies with BSEN 1869 (Kit Mark)
- Container size 30 x 16 x 4cms
- Pull tab to deploy

Part No.	39816